

UV-C DISINFECTION SYSTEMS

FLEX INOX UV-C



With 4 connections!

The Flex UV-C is an excellent solution when multiple flexible installation options are required.

- Multiple installation options thanks to the connection options.
- Including 63mm PVC connection fittings with adaptors to 50mm/1½" fem. threading.
- Including hose connectors 1½" – 40/32/25mm.
- The length of the disinfection system is only 85cm.



T5 40 W

for more lamp information see page 21-23

Item No.	Type	UV-C Lamp	Pond volume	Max. flow	Max. Press.
XE04402.1	Flex INOX UV-C 40 W	40 W T5	40.000 l	20 m³/h - 330 l/min	2 bar
XE04752.1	Flex INOX UV-C 75 W	75 W T5	75.000 l	25 m³/h - 417 l/min	2 bar

FLEX INOX UV-C SPARE PARTS

Item No.	Type	Part
XE04402.1	Flex INOX UV-C 40 W	
XE04752.1	Flex INOX UV-C 75 W	
F980078BU	Lamp VGE T5 40 W 4P Base F(bu)	K
F980079BU	Lamp VGE T5 75 W 4P Base G	K
QG017	Quartz Glass VSC 695 x 25 mm 40/75 W AM	M
3902041	O-ring NBR 56x3	P
EP040012	Electrics UV-C 40 W	L
EP075017	Electrics UV-C 75 W	L
H170009	Housing Black UV-C 40/75 W RVS 304	H
E800940	3-way connection 63 mm black	I
E800941	O-ring for 3-way connection 63 mm	G
F990115	Reduction piece 1,5" wire x 63 out 50 in	F
3902046	Sealing ring 1½"	J
E801128	Universal adaptor 1½" 40 x 32 x 25 mm clear	N
E801107	Tube clip 75 mm PP Black	O
F990196BU	Closing lid Flex UV-C	R
3901045	Nut 70mm x 33.5mm black	S
SP0073	O-ring EPDM 59.99x2.62 Quartz Glass Stabilizer End cap black 32mm	Q

